



# pro clima TESCON® NAIDECK patch

## Double Sided Self-Sealing Patches

TESCON® NAIDECK patch is a double-sided self-sealing patch, designed to seal penetrations of point fixings such as façade clips, brick ties and attachment fasteners. It provides the ultimate protection within windtight and watertight WRB systems at high wind pressures. It is flexible, and comes in two pre-cut sizes, with a simple-to-remove release paper, ensuring maximum productivity during installation. It forms essential part of all commercial façade systems for a durable seal around any nail or screw penetrations and can be fixed directly to your weather resistive barrier (WRB).

- ✓ Ultimate water resistance for façades
- ✓ Weathertight penetrations in WRB layers
- ✓ Self-sealing around nail and screw penetrations
- ✓ Reinforced for extra strength
- ✓ Double sided for connection strength and durability



02 2025



NEW ZEALAND  
0800 PRO CLIMA (776 254)  
Technical: [support@proclima.co.nz](mailto:support@proclima.co.nz)  
General: [welcome@proclima.co.nz](mailto:welcome@proclima.co.nz)  
[www.proclima.co.nz](http://www.proclima.co.nz)

AUSTRALIA  
1800 PRO CLIMA (776 254)  
[support@proclima.com.au](mailto:support@proclima.com.au)  
[welcome@proclima.com.au](mailto:welcome@proclima.com.au)  
[www.proclima.com.au](http://www.proclima.com.au)





# pro clima TESCON® NAIDECK patch

## Double Sided Self-Sealing Patches

### Technical Data

Carrier material:	butyl rubber
Release material:	siliconised paper both sides
Temperature resistance:	long term -20 °C to +80 °C
Installation temperature:	from +5 to +35 °C
Thickness:	<1 mm
Colour:	black
Storage:	cool and dry

### IMPORTANT INFORMATION

- Self-sealing when compressed between two rigid materials. Screw and nail penetrations will be sealed during the fixing process.
- Proven to enhance resistance to driving rain through fixings on WRB penetrations in façade tests, according to AS/NZS 4284 and E2/AS1.
- Pro Clima strongly recommends the use of TESCON® NAIDECK patch on all fixings that penetrate facades WRBs.

### PRODUCT DESCRIPTION

TESCON® NAIDECK patch is a double-sided, self-sealing strip for use behind façade clips, mounts, spacers or rails fixed directly to your façade WRB or roofing applications, or where any attachment is fixed to your WRB layer and requires a penetration. Made from butyl, it has excellent self-sealing properties for optimal resistance to driving rain at any fixing point penetration.

### WEATHER EXPOSURE

This product is not designed to be directly exposure to UV or in direct contact with metal cladding, or in face sealed systems. Ideally, it is used in ventilated façades separated from direct contact with the cladding, using thermal breaks or timber. Exterior cladding should be detailed to prevent direct sunlight onto TESCON® NAIDECK patch in service.

### APPLICATION NOTES

This product should be applied to the clip, mount or the like before installing in the correct position. This allows for adjustments and proper location of the fixed object. TESCON® NAIDECK patch is compatible with the pro clima SOLITEX EXTASANA® and SOLITEX EXTASANA ADHERO® membranes, as well as rigid sheathings, rigid wall underlays and rigid air barriers (RAB). TESCON® NAIDECK patch can also be used on roofing systems with other pro clima products such as SOLITEX MENTO® membranes.

### Delivery Form

ID CODE	LENGTH	WIDTH	CONTENTS	Roll	WEIGHT	SALES UNIT
1AR04073	50 mm	50 mm	340 patches	1	1.27 kg	1 roll
1AR04253	100 mm	50 mm	185 patches	1	1.44 kg	1 roll



NEW ZEALAND  
0800 PRO CLIMA (776 254)  
Technical: [support@proclima.co.nz](mailto:support@proclima.co.nz)  
General: [welcome@proclima.co.nz](mailto:welcome@proclima.co.nz)  
[www.proclima.co.nz](http://www.proclima.co.nz)

AUSTRALIA  
1800 PRO CLIMA (776 254)  
[support@proclima.com.au](mailto:support@proclima.com.au)  
[welcome@proclima.com.au](mailto:welcome@proclima.com.au)  
[www.proclima.com.au](http://www.proclima.com.au)

